



US011620181B2

(12) **United States Patent**
Barat et al.

(10) **Patent No.:** **US 11,620,181 B2**
(45) **Date of Patent:** **Apr. 4, 2023**

(54) **UTILITY INFRASTRUCTURE FAULT
DETECTION AND MONITORING**

(71) Applicant: **Gridware Technologies Inc.**, Folsom,
CA (US)

(72) Inventors: **Timothy Jonathan Barat**, Folsom, CA
(US); **Zhenhao Chen**, Oakland, CA
(US); **Prabal Dutta**, Ann Arbor, MI
(US)

(73) Assignee: **Gridware Technologies Inc.**, Walnut
Creek, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/654,988**

(22) Filed: **Mar. 15, 2022**

(65) **Prior Publication Data**
US 2022/0300363 A1 Sep. 22, 2022

Related U.S. Application Data

(60) Provisional application No. 63/200,653, filed on Mar.
19, 2021.

(51) **Int. Cl.**
G05B 23/02 (2006.01)
G06F 11/07 (2006.01)

(52) **U.S. Cl.**
CPC **G06F 11/079** (2013.01); **G05B 23/0218**
(2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,371,540 A * 12/1994 Tamura H04N 5/0675
348/222.1
7,286,812 B2 10/2007 Manis et al.
9,049,103 B2 6/2015 McHann, Jr.
10,228,278 B2 3/2019 Chen et al.
10,579,777 B2 3/2020 Ziavras et al.
(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 2022/198212 9/2022

OTHER PUBLICATIONS


Miyaoka, English translation of Japanese Patent Publication
JP2007010373, published Jan. 18, 2007.*

Primary Examiner — Bernard G Lindsay
(74) *Attorney, Agent, or Firm* — Levine Bagade Han LLP

(57) **ABSTRACT**

A method may include obtaining, at a server or analysis
device, sensor data comprising at least one of vibration data
and impulse data from one or more sensor devices coupled
to a first utility infrastructure; obtaining training sensor data
associated with at least one of the first utility infrastructure
from a previous time period and one or more second utility
infrastructures; comparing the sensor data with the training
sensor data associated with the at least one of the first utility
infrastructure from the previous time period and the one or
more second utility infrastructures; and identifying or pre-
dicting a fault occurrence associated with the first utility
infrastructure based on the comparing the sensor data asso-
ciated with the first utility infrastructure to the training
sensor data associated with the at least one of the first utility
infrastructure from the previous time period and the one or
more second utility infrastructures.

6 Claims, 11 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

10,637,239 B2 4/2020 Neuenschwander
2004/0054921 A1 3/2004 Land, III
2007/0124619 A1* 5/2007 Mizukami G05B 23/027
713/323
2011/0288777 A1* 11/2011 Gupta G06Q 10/06311
702/57
2011/0313726 A1 12/2011 Parthasarathy et al.
2012/0169842 A1* 7/2012 Chuang G08B 13/19682
348/E7.001
2013/0250339 A1* 9/2013 Ming H04N 1/0005
358/1.14
2014/0278150 A1* 9/2014 Baesler E04H 12/00
702/34
2017/0102234 A1* 4/2017 Oshetski G01R 31/088
2017/0227596 A1* 8/2017 Sozer G01R 31/085
2018/0217103 A1* 8/2018 Someda G01N 29/045
2018/0275199 A1 9/2018 Parkin
2020/0160195 A1 5/2020 Strharsky et al.
2020/0293032 A1 9/2020 Wang et al.
2020/0332775 A1 10/2020 Nielsen et al.
2020/0409323 A1* 12/2020 Spalt G06F 17/18
2021/0080514 A1* 3/2021 Beaudet G01R 19/2513
2022/0034847 A1* 2/2022 Spencer G01W 1/00

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 2





FIG. 3A






FIG. 4




FIG. 5




FIG. 6

1

UTILITY INFRASTRUCTURE FAULT DETECTION AND MONITORING

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the benefit of U.S. Provisional Application No. 63/200,653 filed on Mar. 19, 2021, the entirety of which is incorporated herein by reference.

TECHNICAL FIELD

The present disclosure generally relates to the field of utility infrastructure management and, more specifically, to fault detection and monitoring for utility infrastructure.

BACKGROUND

Utility infrastructure may facilitate transportation of energy, such as electricity, to a number of destinations. Utility infrastructure may include telecommunications structures, such as cell towers and telephone poles; electricity infrastructure, such as electricity towers and power lines; and/or energy infrastructure, such as gas pipelines, solar panels, windmills, etc. Utility infrastructure may be adversely affected by extreme weather conditions and/or accidents caused by humans. In some circumstances, such extreme weather conditions and/or human-caused accidents may damage utility infrastructure, which may cause additional damage to an area around the damaged utility infrastructure. In addition, utility infrastructure may deteriorate over time, for example, according to its expected lifespans. In some circumstances, the deterioration of utility infrastructure may be accelerated by various environmental factors, such as moisture or extreme temperatures.

The subject matter claimed in the present disclosure is not limited to embodiments that solve any disadvantages or that operate only in environments such as those described above. Rather, this background is only provided to illustrate one example technology area where some embodiments described in the present disclosure may be practiced.

SUMMARY

According to an aspect of an embodiment, sensor data may be obtained from one or more sensors associated with utility infrastructure. The sensor data associated with the utility infrastructure may be compared to training sensor data associated with one or more utility infrastructures. Identification and/or prediction of one or more faults occurrence associated with the utility infrastructure may be accomplished based on the comparing the sensor data associated with the utility infrastructure to the training sensor data associated with the one or more utility infrastructures, utility infrastructure models, and/or utility infrastructure simulations. The sensor data and information about the associated fault occurrences may be stored and/or transmitted to a data storage. A message describing the faults of the utility infrastructure and/or summarizing the condition of the utility infrastructure may be transmitted to a supervising user.

The object and advantages of the embodiments will be realized and achieved at least by the elements, features, and combinations particularly pointed out in the claims. It is to be understood that both the foregoing general description and the following detailed description are explanatory and are not restrictive of the invention, as claimed.

2

In some embodiments, a method comprises: obtaining, at a server or an analysis device, sensor data including at least one of vibration data and impulse data from one or more sensor devices coupled to a first utility infrastructure; obtaining training sensor data associated with at least one of the first utility infrastructure from a previous time period and one or more second utility infrastructures; comparing the sensor data associated with the training sensor data with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures; identifying or predicting a fault occurrence associated with the first utility infrastructure based on the comparing the sensor data associated with the first utility infrastructure to the training sensor data associated with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures; and transmitting a message describing the fault occurrence of the first utility infrastructure or summarizing a condition of the first utility infrastructure from the server or the analysis device to a computing device.

In some embodiments, the method further comprises determining a normal operating condition for the first utility infrastructure based on the comparing the sensor data associated with the first utility infrastructure to the training sensor data associated with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures.

In some embodiments, the fault occurrence includes at least one of damage to a component associated with the first utility infrastructure and environmental damage near the first utility infrastructure.

In some embodiments, the fault occurrence is caused by at least one of physical contact between one or more objects and the first utility infrastructure.

In some embodiments, the fault occurrence is caused by high-voltage arcing occurring at the first utility infrastructure.

In some embodiments, the fault occurrence is caused by break-out of a fire near the first utility infrastructure.

In some embodiments, the fault occurrence includes a deterioration of the first utility infrastructure, wherein the vibration data obtained from the one or more sensor devices includes a present first oscillatory pattern of the first utility infrastructure due to current flowing through channels supported by or otherwise coupled to the first utility infrastructure, wherein the training sensor data includes at least one of a previous first oscillatory pattern of the first utility infrastructure due to current flowing through the channels obtained during the previous time period, a present second oscillatory pattern of a second utility infrastructure due to current flowing through channels supported by or otherwise coupled to the second utility infrastructure, and a previous second oscillatory pattern of the second utility infrastructure due to current flowing through channels supported by or otherwise coupled to the second utility infrastructure obtained during the previous time period, and wherein the fault occurrence is identified or predicted when the present first oscillatory pattern is attenuated in comparison to at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern.

In some embodiments, the first utility infrastructure is made in part of wood and wherein the deterioration of the first utility infrastructure is caused by at least one of heart rot, shell rot, rot caused by an insect or animal, and termite damage of the wood making up at least part of the first utility infrastructure.

In some embodiments, the fault occurrence includes a deterioration of the first utility infrastructure, wherein the vibration data obtained from the one or more sensor devices includes a present first oscillatory pattern of the first utility infrastructure in response to rain or wind affecting the first utility infrastructure, wherein the training sensor data includes at least one of a previous first oscillatory pattern of the first utility infrastructure in response to rain or wind affecting the first utility infrastructure during the previous time period and obtained during the previous time period, a present second oscillatory pattern of a second utility infrastructure in response to rain or wind affecting the second utility infrastructure, and a previous second oscillatory pattern of the second utility infrastructure in response to rain or wind affecting the second utility infrastructure during the previous time period and obtained during the previous time period, and wherein the fault occurrence is identified or predicted when the present first oscillatory pattern is attenuated in comparison to at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern.

In some embodiments, the sensor data further includes at least one of structure-orientation data, gyration data, temperature data, humidity data, atmospheric pressure data, precipitation data, wind velocity data, smoke density data, particulate matter data, gas composition data, magnetic field data, electric field data, microwave radiation data, infrared radiation data, ultraviolet radiation data, visible luminosity data, electromagnetic spectroscopy data, mechanical spectroscopy data, audio data, image data, and video data relating to the utility infrastructure.

In some embodiments, each of the one or more sensor devices includes at least one of a vibrometer, an accelerometer, a gyroscope, an acoustic microphone, a video camera, an ambient temperature sensor, a barometer, a hygrometer, a magnetometer, a smoke detector, a visible light meter or photometer, an ultraviolet (UV) light detector, an infrared (IR) light detector, an anemometer or wind sensor, a particulate meter or counter, an electrometer, a multi-field electromagnetic field (EMF) meter, a radio frequency (RF) meter, and a spectrometer.

In some embodiments, the fault occurrence of the first utility infrastructure is identified or predicted by at least one of analog signal processing and digital signal processing of the sensor data and the training sensor data and comparing the processed sensor data against the processed training sensor data.

In some embodiments, the fault occurrence of the first utility infrastructure is identified or predicted by feeding the sensor data to at least one of a supervised learning model and an unsupervised learning model and obtaining a prediction from the at least one of the supervised learning model and the unsupervised learning model concerning the fault occurrence, and wherein the supervised learning model and the unsupervised learning models are trained using the training sensor data.

In some embodiments, each of the one or more sensor devices is coupled to the first utility infrastructure at a position at least 3.0 meters above ground level.

In some embodiments, each of the one or more sensor devices is coupled to the first utility infrastructure via a bracket fixedly fastened to an exterior side of the first utility infrastructure, and wherein at least one of a vibration and impulse sustained by the first utility infrastructure or a channel supported by or coupled to the first utility infrastructure is passed through the first utility infrastructure via the bracket to each of the one or more sensor devices.

In some embodiments, disclosed is a system comprising: one or more sensor devices coupled to a first utility infrastructure, the sensor devices including: an enclosure; one or more internal sensors positioned inside of the enclosure and one or more external sensors positioned at least partly outside of the enclosure; one or more antennae; and one or more energy-storage features; one or more processors of a server or analysis device; and one or more non-transitory computer-readable storage media of the server or analysis device configured to store instructions that, in response to being executed, cause the one or more processors to perform operations, the operations including: obtaining sensor data including at least one of vibration data and impulse data from one or more sensor devices coupled to a first utility infrastructure; obtaining training sensor data associated with at least one of the first utility infrastructure from a previous time period and one or more second utility infrastructures; comparing the sensor data with the training sensor data associated with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures; identifying or predicting a fault occurrence associated with the first utility infrastructure based on the comparing the sensor data associated with the first utility infrastructure to the training sensor data associated with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures; and transmitting a message, to a computing device, describing the fault occurrence of the first utility infrastructure or summarizing a condition of the first utility infrastructure.

In some embodiments, the fault occurrence includes a deterioration of the first utility infrastructure, wherein the vibration data obtained from the one or more sensor devices includes a present first oscillatory pattern of the first utility infrastructure due to current flowing through channels supported by or coupled to the first utility infrastructure, wherein the training sensor data includes at least one of a previous first oscillatory pattern of the first utility infrastructure due to current flowing through the channels obtained during the previous time period, a present second oscillatory pattern of a second utility infrastructure due to current flowing through channels supported by or coupled to the second utility infrastructure, and a previous second oscillatory pattern of the second utility infrastructure due to current flowing, obtained during the previous time period, through channels supported by or coupled to the second utility infrastructure, and wherein the fault occurrence is identified or predicted when the present first oscillatory pattern is attenuated in comparison to at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern.

In some embodiments, the first utility infrastructure is made in part of wood and wherein the deterioration of the first utility infrastructure is caused by at least one of heart rot, rot caused by an insect or animal, and termite damage of the wood making up at least part of the first utility infrastructure.

In some embodiments, the fault occurrence includes a deterioration of the first utility infrastructure, wherein the vibration data obtained from the one or more sensor devices includes a present first oscillatory pattern of the first utility infrastructure in response to rain or wind affecting the first utility infrastructure, wherein the training sensor data includes at least one of a previous first oscillatory pattern of the first utility infrastructure in response to rain or wind affecting the first utility infrastructure during the previous time period and obtained during the previous time period, a

present second oscillatory pattern of a second utility infrastructure in response to rain or wind affecting the second utility infrastructure, and a previous second oscillatory pattern of the second utility infrastructure in response to rain or wind affecting the second utility infrastructure during the previous time period and obtained during the previous time period, and wherein the fault occurrence is identified or predicted when the present first oscillatory pattern is attenuated in comparison to at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern.

In some embodiments, disclosed are one or more non-transitory computer-readable storage media configured to store instructions that, in response to being executed, cause one or more processors to perform operations, the operations including: obtaining sensor data including at least one of vibration data and impulse data from one or more sensor devices coupled to a first utility infrastructure; obtaining training sensor data associated with at least one of the first utility infrastructure from a previous time period and one or more second utility infrastructures; comparing the sensor data with the training sensor data associated with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures; identifying or predicting a fault occurrence associated with the first utility infrastructure based on the comparing the sensor data associated with the first utility infrastructure to the training sensor data associated with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures; and transmitting a message describing the fault occurrence of the first utility infrastructure or summarizing a condition of the first utility infrastructure.

BRIEF DESCRIPTION OF THE DRAWINGS

Example embodiments will be described and explained with additional specificity and detail through the accompanying drawings in which:

FIG. 1A illustrates a perspective view of an example embodiment of a sensor device according to the present disclosure;

FIG. 1B illustrates a perspective view of the example embodiment of the sensor device with part of an enclosure removed for ease of viewing;

FIG. 1C illustrates a perspective view of another example embodiment of the sensor device;

FIG. 1D illustrate the sensor device of FIG. 1C coupled to an embodiment of a utility infrastructure.

FIG. 1E illustrate the sensor device of FIG. 1C coupled to another embodiment of a utility infrastructure.

FIG. 1F illustrate the sensor device of FIG. 1C coupled to yet another embodiment of a utility infrastructure.

FIG. 2 illustrates a plurality of utility infrastructures having sensor devices coupled to such utility infrastructures;

FIG. 3A illustrates a first fault detection scenario for a given utility infrastructure including the sensor device;

FIG. 3B illustrates a second fault detection scenario for a given utility infrastructure including the sensor device;

FIG. 4 is a diagram illustrating one embodiment of a system for identifying or predicting a fault occurrence;

FIG. 5 is a flowchart illustrating an embodiment of a method for identifying or predicting a fault occurrence; and

FIG. 6 is an example computing system.

DETAILED DESCRIPTION

Damage to utility infrastructure may cause localized and/or widespread harm to property, people, and/or the

environment. For example, damage to electricity distribution systems may lead to forest fires, destruction of nearby structures, and/or pose electrocution risks to passing humans. A utility company may be incapable of or slow to identify the cause of the damage to the utility infrastructure. In such cases, the utility company may decide to de-energize large portions of the utility infrastructure as a preventative measure. The utility company may also be unable to predict which situations warrant shutting off the utility infrastructure ahead of time. The inability to ascertain when damage to the utility infrastructure is likely and/or the extent of the damage to the utility infrastructure may adversely affect those relying on the utility infrastructure.

The embodiments described in the present disclosure may relate to, among other things, a method of monitoring and assessing the condition of utility infrastructure and facilitate more accurate prediction and/or assessment of damage to utility infrastructure. In some embodiments, sensor data may be obtained from one or more sensors associated with the utility infrastructure. The sensor data may be analyzed to identify and/or predict one or more faults of the utility infrastructure. An alert message describing the predicted faults of the support structure may be generated and sent to a user and/or an automated system in control of the utility infrastructure.

Embodiments of the present disclosure are explained with reference to the accompanying figures.

FIG. 1A illustrates a perspective view of an example embodiment of a sensor device **100** according to the present disclosure. The sensor device **100** may include an enclosure **110**. In some embodiments, the sensor device **100** may include one or more solar cells **115**. As illustrated, in some aspects, the solar cells **115** may be positioned on one or more surfaces of the enclosure **110**, although other mounting configurations may be implemented. In these and other embodiments, the sensor device **100** may include one or more antennae **120**, sensors (e.g., a wind sensor **132** and/or environmental sensors **134**), one or more built-in cameras **142**, and/or one or more microphones **144**.

One or more sensors, batteries, and/or other components may be positioned at least partially inside of the enclosure **110**. The enclosure **110** may protect components that may be unsuited to weather exposure. In some embodiments, the enclosure **110** may be made of a material capable of withstanding typical weather conditions and/or extreme weather conditions without exposing components included in the enclosure **110** to such weather conditions. For example, the enclosure **110** may be made of polyvinyl chloride, low density polyethylene, etc. In addition, for example, the enclosure **110** may be made of a metal, such as stainless steel, cast iron, aluminum, etc. Also, for example, the enclosure **110** may be made of carbon fiber, or other material.

In some embodiments, the enclosure **110** may be shaped such that the enclosure **110** may be attached to utility infrastructure and/or support structures for the utility infrastructure. For example, the shape of the enclosure **110** may correspond to a component of the utility infrastructure and/or may correspond to the shape of a support structure.

One or more external sensors and/or other components may be positioned at least partially outside of the enclosure **110**, for example, on one or more outer surfaces of the enclosure **110**. Such components may not require protection of the enclosure **110**, for example, from weather exposure or other considerations.

In some embodiments, the solar cells **115** may be attached to one or more of the surfaces of the enclosure **110**. The solar

cells **115** may generate and/or store energy to be supplied to one or more components of the sensor device **100**, such as the sensors and/or the battery. Additionally or alternatively, the sensor device **100** may include other energy generation features and/or energy storage features, such as rechargeable lithium-ion batteries. Additionally or alternatively, the sensor device **100** may be coupled to the utility infrastructure such that the sensor device **100** obtains energy from the utility infrastructure.

The sensor device **100** may include one or more antennae **120** and/or sensors attached to the enclosure **110** capable of communicating via cellular signals, radio signals, Bluetooth signals, Wi-Fi signals, and/or other forms of signaling. The antennae **120** may be communicatively coupled to a utility network such that a user may monitor activity and/or sensor data collected by the sensor device **100**. In some embodiments, the antennae **120** may transmit collected sensor data to a server, such as a cloud server, for data analysis as described in further detail below in relation to FIG. **4**.

Some of the sensors may be positioned exterior of the enclosure such as any sensors that benefit from being positioned on an exterior surface of the enclosure **110** rather than inside of the enclosure **110**. In these and other embodiments, data collection may be facilitated and/or made more accurate by positioning some sensors on the exterior surface of the enclosure **110**. Additionally or alternatively, the sensors may be attached at a first location on the utility infrastructure while being communicatively coupled to a sensor device **100** attached at a second location on the utility infrastructure.

In some embodiments, the sensor data collected by the wind sensor **132** and/or the environmental sensors **134** may be analyzed to determine weather conditions experienced at a given location and/or time by measuring parameters including temperature, humidity, air pressure, solar intensity, wind velocity, smoke density, etc. The sensor data relating to weather conditions may be organized with respect to location and/or time to analyze the weather around a utility infrastructure system. In these and other embodiments, averaging the weather-related sensor data for a number of sensor devices **100** in a given area may improve detection and mapping of microclimates experienced by one or more of the sensor devices **100**, which may facilitate pinpointing of non-uniform equipment degradation and irregular load behaviors. Additionally or alternatively, analysis of weather-related sensor data may facilitate making better-informed decisions regarding operations of the utility infrastructure.

In some embodiments, the sensor device **100** may be configured to perform preliminary processing and/or verification of the collected sensor data before transmitting the sensor data for further analysis. For example, the sensor device **100** may include the cameras **142** and/or the microphones **144**, which may capture image and/or audio data, respectively, relating to the utility infrastructure. In some embodiments, the sensor device **100** may be configured to capture the image and/or audio data in response to sensor data collected by the wind sensor **132** and/or one or more of the environmental sensors **134** exceeding a given threshold, falling below a given threshold, equaling a given value, following a given trend, displaying a predetermined pattern, etc. In these and other embodiments, the captured image and/or audio data may be transmitted to a user and/or computing device for fault-occurrence verification and/or analysis.

FIG. **1B** illustrates a perspective view of the example embodiment of the sensor device **100** according to the

present disclosure. In FIG. **1B**, a portion of the enclosure **110** is not shown to illustrate components of the sensor device **100** that may be included inside of the enclosure **110**. In some embodiments, one or more internal sensors **136** and/or one or more batteries **140** may be included inside of the enclosure **110**. In these and other embodiments, the internal sensors **136**, the environmental sensors **134**, and/or the one or more batteries **140** may be coupled to a circuit board **150**.

In some embodiments, the internal sensors **136** may comprise a 3-axis accelerometer, a gyroscope (e.g., a 3-axis gyroscope), a vibrometer, a magnetometer (e.g., a multi-axis magnetometer), an electrometer, an electromagnetic field (EMF) meter (e.g., a multi-field EMF meter), a radio frequency (RF) meter, a spectrometer, or a combination thereof. In these and other embodiments, the environmental sensors **134** may comprise an ambient temperature sensor, a barometer, a hygrometer, a smoke detector, a visible light meter, an ultraviolet (UV) light detector, an infrared (IR) light detector, an anemometer or wind sensor, a particulate meter/counter, or a combination thereof. Although FIGS. **1A** and **1B** show the environmental sensors **134** as being separate from the internal sensors **136**, it is contemplated by this disclosure and it should be understood by one of ordinary skill in the art that any of the environmental sensors **134** can also be positioned or housed within the enclosure **110** and that any of the internal sensors **136** can be positioned or located, at least partly, outside of the enclosure **110**.

As will be discussed in more detail in later sections, the environmental sensors **134**, the wind sensor **132**, the internal sensors **136**, the built-in cameras **142**, and the acoustic microphones **144** can work together to measure and monitor various conditions and states of the utility infrastructure **200** in response to any external forces applied to the utility infrastructure **200**, any weather-related phenomena near the utility infrastructure **200**, any weather-related or fire-related damage to a surrounding environment (including trees and other plant matter or vegetation) near the utility infrastructure **200**, any spontaneous electrical events (e.g., high-voltage arcing) occurring at or near the utility infrastructure **200**, any geologic events occurring near the utility infrastructure **200**, and/or any internal damage or deterioration sustained by the utility infrastructure **200**.

In some embodiments, a number of sensor devices **100** may be positioned on various support structures and/or components of the utility infrastructure to facilitate sensor data collection focused on the various support structures and/or components (e.g., sensor data collection focused on a given transformer attached to an electricity pole). In these and other embodiments, the accelerometer may measure vibrations experienced by the sensor device **100**, which may be correlated to vibrations experienced by the utility infrastructure and/or associated support structures. Additionally or alternatively, a gyroscope may measure orientation and/or changes to the orientation of the sensor device **100** to assess positioning of the utility infrastructure and/or support structures. The sensor data collected by the internal sensors **136** may be sent to a server to analyze the conditions of the utility infrastructure. In some embodiments, the sensor data may be tagged with location information and/or time information such that data trends between geographic regions and/or over one or more periods of time may be established. In some embodiments, the sensor device **100** may be configured to capture image and/or audio data in response to the sensor data collected by the internal sensors **136** exceeding a given threshold, falling below a given threshold, equaling

a given value, following a given trend, displaying a predetermined pattern, etc. as described above in relation to FIG. 1A.

In some embodiments, the internal sensors 136 may include one or more tactile switches to prevent physical tampering with the sensor device 100. The tactile switches may include a first setting indicating the sensor device 100 is secure and a second setting indicating the sensor device 100 is compromised. In some embodiments, the tactile switches may be engaged in the first setting when the sensor device 100 is coupled to the utility infrastructure, the enclosure 110 is securely closed, the battery 140 is operational, and/or other operating conditions are satisfied. Responsive to physical tampering with the sensor device 100, the tactile switches may engage in the second setting. In these and other embodiments, the tactile switches being engaged in the second setting may trigger transmission of sensor data indicating the sensor device 100 is compromised.

In some embodiments, the sensor device 100 may include the battery 140 to provide a source of backup energy in the event the solar cells 115 fail to function. In some embodiments, the battery 140 may be coupled to the solar cells 115 such that the solar cells 115 provide energy to the battery 140 during normal operations of the sensor device 100. Responsive to failure of the solar cells 115, the battery 140 may provide energy to the sensor device 100. In these and other embodiments, the sensor device 100 may include a number of batteries 140 and/or a type of batteries such that the backup energy provided by the batteries 140 lasts for a given duration of time (e.g., the sensor device 100 may be powered by the batteries 140 for one day, one week, two weeks, etc.).

FIG. 1C illustrates a perspective view of another example embodiment of the sensor device 100. The sensor device 100 may operate the same as the sensor devices 100 shown in FIGS. 1A-1B. The sensor device 100 may include a UV-resistant polymer-based enclosure 110. For example, the enclosure 110 may be made of polyvinyl chloride, low density polyethylene, etc. In addition, for example, the enclosure 110 may be made of a metal, such as stainless steel, cast iron, aluminum, etc. Also, for example, the enclosure 110 may be made of carbon fiber, or other material.

In some embodiments, the sensor device 100 may include one or more solar cells or a solar panel 115. As shown in FIG. 1C, the solar cells or solar panel 115 may be tilted or angled so the solar cells or the solar panel 115 catches more sunlight. At least part of the enclosure 110 may be configured or otherwise designed as an angled support structure for the solar cells or the solar panel 115.

In some embodiments, the solar panel 115 may be made in part of polycrystalline photovoltaic solar cells. For example, the solar panel 115 can be a 3 W polycrystalline photovoltaic solar panel.

The solar cells 115 or the solar panel 115 may generate and/or store energy to be supplied to one or more components of the sensor device 100, such as the sensors and/or the battery 140. Additionally or alternatively, the sensor device 100 may include other energy generation features and/or energy storage features, such as rechargeable lithium-ion batteries. In some embodiments, the battery 140 may be a rechargeable lithium iron phosphate (LiFePO₄) battery. In these and other embodiments, the battery 140 may be a 32 watt-hour high-capacity battery.

Additionally or alternatively, the sensor device 100 may be coupled to the utility infrastructure such that the sensor device 100 obtains energy from the utility infrastructure.

In these and other embodiments, the sensor device 100 may include one or more antennae, internal sensors 136 and environmental sensors 134, one or more built-in cameras 142, and/or one or more acoustic microphones 144.

In some embodiments, the internal sensors 136 can comprise a 3-axis accelerometer, a gyroscope (e.g., a 3-axis gyroscope), a vibrometer, a magnetometer (e.g., a multi-axis magnetometer), an electrometer, an electromagnetic field (EMF) meter (e.g., a multi-field EMF meter), a radio frequency (RF) meter, a spectrometer, or a combination thereof. In these and other embodiments, the environmental sensors 134 can comprise an ambient temperature sensor, a barometer, a hygrometer, a smoke detector, a visible light meter, an ultraviolet (UV) light detector, an infrared (IR) light detector, an anemometer or wind sensor, a particulate meter/counter, or a combination thereof. Although FIG. 1C shows the environmental sensors 134 as being separate from the internal sensors 136, it is contemplated by this disclosure and it should be understood by one of ordinary skill in the art that any of the environmental sensors 134 can also be positioned or housed within the enclosure 110 and that any of the sensors listed under internal sensors 136 in FIG. 1C can be positioned or located, at least partly, outside of the enclosure 110.

The environmental sensors 134, the internal sensors 136, the built-in cameras 142, and the acoustic microphones 144 can work together to measure and monitor various conditions and states of the utility infrastructure 200 in response to any external forces applied to the utility infrastructure 200, any weather-related phenomena near the utility infrastructure 200, any weather-related or fire-related damage to a surrounding environment (including trees and other plant matter or vegetation) near the utility infrastructure 200, any spontaneous electrical events (e.g., high-voltage arcing) occurring at or near the utility infrastructure 200, any geologic events occurring near the utility infrastructure 200, and/or any internal damage or deterioration sustained by the utility infrastructure 200.

In some embodiments, the battery 140 may be included inside of the enclosure 110. In these and other embodiments, the internal sensors 136, the environmental sensors 134, and/or the battery 140 may be coupled to a printed or flexible circuit board (e.g., the circuit board 150, not shown in FIG. 1C).

In some embodiments, the sensor device 100 may include one or more tactile switches to prevent physical tampering with the sensor device 100. The tactile switches may include a first setting indicating the sensor device 100 is secure and a second setting indicating the sensor device 100 is compromised. In some embodiments, the tactile switches may be engaged in the first setting when the sensor device 100 is coupled to the utility infrastructure, the enclosure 110 is securely closed, the battery 140 is operational, and/or other operating conditions are satisfied. Responsive to physical tampering with the sensor device 100, the tactile switches may engage in the second setting. In these and other embodiments, the tactile switches being engaged in the second setting may trigger transmission of sensor data indicating the sensor device 100 is compromised.

FIGS. 1D-1F illustrate the sensor device 100 coupled to an embodiment of a utility infrastructure 200. As shown in FIGS. 1D-1F, the utility infrastructure 200 may be or comprise a wooden utility pole (e.g., an electrical utility pole) or power pole.

As will be discussed in more detail in later sections, when the utility infrastructure 200 is made, at least in part, of wood, the utility infrastructure 200 (e.g., a wooden utility

pole or power pole) can be subject to deterioration or weakening as a result of rot or decay. For example, the utility infrastructure **200** can undergo or be subject to deterioration as a result of heart rot, shell rot, rot caused by an insect or animal, and/or termite damage. Heart rot is a fungal disease that causes the decay of wood at the center (what is known as the heartwood). Shell rot is a decay or softening of the outer portion of the wood surrounding the heartwood (known as the sapwood). Wooden utility poles or power poles can be subject to external decay (shell rot), internal decay (heart rot), or insect damage along portions of the wood not treated with preservatives or sealant or where the preservative or sealant has been removed due to cracks, cuts or holes drilled into the wood.

As shown in FIGS. 1D-1F, the sensor device **100** can be coupled to the utility infrastructure **200** (e.g., the utility pole) via a bracket **160** fixedly fastened or attached to an exterior side of the utility infrastructure **200**. As will be discussed in more detail in later sections, a vibration or impulse sustained by the utility infrastructure **200** or one or more channels **200** (e.g., power lines) coupled to and supported by the utility infrastructure **200** can be passed through the utility infrastructure **200** via the bracket **160** to be detected by the sensor device **100**.

For example, the bracket **160** can be fastened or otherwise attached to the exterior side of the utility infrastructure via fasteners, screws, and/or bolts. Once the bracket **160** is securely fastened or attached to the exterior side of the utility infrastructure **200**, the sensor device **100** can be detachably coupled to the bracket **160**, for example, by sliding a part of the enclosure **110** on to the bracket **160** via an interlocking mechanism, a latch mechanism, and/or an interference fit. In other embodiments, the sensor device **100** can be fastened to the bracket **160** via fasteners or other types of mechanical couplers.

The sensor device **100** can be coupled to the utility infrastructure **200** at a position at least 3.0 meters above ground level. (e.g., 3.5 meters to 4.5 meters above ground level). In some embodiments, the sensor device **100** can be coupled to the utility infrastructure **200** along an upper or vertically upper half of the utility infrastructure **200**. In other embodiments, the sensor device **100** can be coupled to the utility infrastructure **200** at a halfway point or vertical halfway point along the utility infrastructure **200**. In all such embodiments, the sensor device **100** is coupled to the utility infrastructure **200** at least 3.0 meters above ground level.

One technical problem faced by the applicants is how to couple the sensor device **100** to the utility infrastructure **200** such that enough of the vibrations and/or impulses sustained by the utility infrastructure **200** and enough of the environmental influences affecting the utility infrastructure **200** is detectable by the sensor device **100** to a degree that can aid in fault detection. One technical solution discovered and developed by the applicants is to couple the sensor device **100** to the utility infrastructure **200** at a position along an exterior side of the utility infrastructure **200** at least 3.0 meters above ground level. The sensor device **100** can be coupled to the utility infrastructure **200** via a bracket **160** securely fastened to the exterior side of the utility infrastructure.

FIG. 2 illustrates a plurality of utility infrastructures **200** including a first utility infrastructure **200A** and a second utility infrastructure **200B**. Each of the utility infrastructures **200** can have at least one sensor device **100** coupled to the utility infrastructure **200**. The sensor **100** shown in FIG. 2 can represent any of the sensor devices **100** depicted in FIGS. 1A-1F.

For purposes of this disclosure, any references to the utility infrastructure **200** (including any of the first utility infrastructure **200A**, the second utility infrastructure **200B**, etc.) may refer to a support structure **210**, such as a utility or electrical pole, a cell tower, etc., used to support certain utility equipment and/or communication equipment. Moreover, any references to the utility infrastructure **200** (including any of the first utility infrastructure **200A**, the second utility infrastructure **200B**, etc.) may refer to channels **220** (e.g., power lines, communication lines, etc.) supported by and coupled to the support structure **210**, which may transmit electricity, communication signals, etc. For example, the channels **220** may include power lines of an electricity transport system. In some embodiments, sensor data collected by the sensor devices **100** may be transmitted to a server **240**, an analysis device **250**, or a combination thereof via a wireless communication network **230** (see also, FIG. 4).

In some embodiments, the sensor device **100** may be coupled to the support structure **210**. For example, the sensor device **100** may be coupled to the support structure **210** such that the sensor device **100** is positioned above ground level relative to a base of the support structure **210**. As previously discussed, the sensor device **100** may be coupled to the support structure **210** at a position along an exterior side of the support structure **210** at least 3.0 meters above ground level. The sensor device **100** may be coupled to the support structure **210** via a bracket **160** (not shown in FIG. 2, see FIGS. 1D-1F).

In some embodiments, the sensor device **100** may be positioned at the top of the support structure **210**.

Sensor data collected at different positions along the support structure **210** may differ depending on positioning of the sensor device **100**. For example, vibration data may differ in terms of vibration frequency, intensity of vibrations, timing of vibration occurrence, etc. In these and other embodiments, a plurality of sensor devices **100** may be coupled to the same support structure **210** such that varying quantities and qualities of sensor data may be collected to improve detection frequency, analysis accuracy of the sensor data, etc.

Although not shown in FIG. 2, it is contemplated by this disclosure that the sensor device **100** may be coupled to the channels **220** of the utility infrastructure **200**. For example, the sensor device **100** may be coupled to one or more of the power lines. In such an example, the sensor device **100** may be configured to detect vibrations along the power lines, vibrations due to current flowing through the power lines, and/or other metrics that may indicate operability of the power lines.

In embodiments where the utility infrastructure **200** is part of an electrical utility system, current flowing through channels **220** coupled to a support structure **210** can cause the support structure **210** or other components of the utility infrastructure **200** to vibrate. These vibrations can propagate to a sensor device **100** attached, affixed, or otherwise coupled to the support structure **210** such that such vibrations can be detected by at least the internal sensors **136** of the sensor device **100** in the form of vibration data. As will be discussed in more detail in later sections, at least one of the server **240** and the analysis device **250** can identify and predict a fault occurrence associated with the utility infrastructure **200** by comparing the vibration data (along with other sensor data) collected by the sensor device **100** coupled to the utility infrastructure **200** against other vibration data/sensor data collected by other sensor devices **100** coupled to other utility infrastructures **200**.

In some embodiments, the sensor data collected by the sensor devices **100** may be transmitted to the server **240** and/or the analysis device **250** via the network **230**. One or more computing devices may also be communicatively coupled to the network **230**.

FIG. 3A illustrates a first fault detection scenario **300a** including the sensor device **100** according to the present disclosure. The first fault detection scenario **300a** may include a support structure **310** and channels **320**, which may be the same as or similar to the support structure **210** and the channels **220** of the utility infrastructure **200**, respectively. As such the illustrated support structure **310** may include utility poles, electricity poles, etc., and/or the illustrated channels **320** may include power lines. The first fault detection scenario **300a** may include a first fault cause **332** in which a branch and/or another object contacts the channels **320**. Additionally or alternatively, the first fault detection scenario **300a** may include a second fault cause **334** in which a fire breaks out near the support structures **310** and/or the channels **320**. The first fault cause **332** and/or the second fault cause **334** may cause vibrations **340** and/or other physical phenomena to be experienced by the utility infrastructure, which may be detected and collected by the sensor devices **100**.

In some circumstances, an object may contact the channels **320** as depicted by the first fault cause **332**. For example, the object may include a branch from a tree overhanging the utility infrastructure, nearby debris, wind-borne objects, passing wildlife, etc. Contact between the object and the channels **320** may cause vibrations **340** to propagate through the channels **320** and/or the support structures **310**, which may be detected by the sensor devices **100**. Furthermore, contact between the object and the channels **320** occurring from different directions may cause different vibration sequences. For example, branches falling on top of the channels **320** may result in different vibration patterns compared to branches thrown at the channels **320** from below.

Sensor devices **100** may detect various events that provide details about the first fault cause **332**. For example, built-in cameras and/or microphones, such as the built-in cameras **142** and/or the microphones **144**, may capture images and/or sound to provide additional information that improves fault detection and/or analysis. The built-in cameras may be configured to capture images responsive to collection of sensor data that may indicate the presence of or potential occurrence of faults. Additionally or alternatively, the built-in cameras may capture images at set intervals. The image data may allow a user monitoring the utility infrastructure to identify false positives and/or verify operability of the sensor devices. The built-in microphones associated with one or more of the sensor devices **100** may capture sound information that allow for further fault detection and analysis. For example, built-in microphones associated with two or more sensor devices **100** may capture sounds relating to the same event (e.g., a lightning strike) and facilitate identification of the location at which the event occurred based on differences in timing, frequency, intensity, etc. between the sounds captured by each of the sensor devices **100**.

In some circumstances, environmental events may occur in the first fault detection scenario **300a** as depicted by the second fault cause **334**. In these and other embodiments, the second fault cause **334** may be caused by and/or otherwise related to the first fault cause **332**. For example, the second fault cause **334** may include a fire breaking out near the support structures **310** and/or the channels **320**. The fire may be caused by damage to the channels **320** of the utility

infrastructure resulting in high-voltage arcing and ignition of nearby vegetation. The physical phenomena associated with the second fault cause **334** may be detected by the sensor devices **100**. In other circumstances, the second fault scenario **334** may be unrelated to the first fault scenario **332**. For example, a fire may be caused by lightning, human error, and/or other causes.

In some embodiments, the second fault cause **334** and the first fault cause **332** may occur simultaneously or within a short time period. The sensor data collected by the sensor devices **100** may correspond to physical phenomena related to the second fault cause **334** and/or the first fault cause **332**. Analysis of the sensor data to determine the condition of the utility infrastructure is described in more detail below in relation to FIG. 4.

FIG. 3B illustrates a second fault detection scenario **300b** for a given utility infrastructure including the sensor device **100** according to the present disclosure. The second fault detection scenario **300b** may include a third fault cause **336** in which the channels **320** are damaged and/or disconnected. Additionally or alternatively, the second fault detection scenario **300b** may include a fourth fault cause **338** in which one or more of the support structures **310** are damaged.

In some circumstances, damage to the utility infrastructure may include destruction of one or more of the channels **320** as depicted in the third fault cause **336**. Destruction of the channels **320** may cause physical phenomena detectable by one or more of the sensor devices **100**. In these and other embodiments, the destruction of the channels **320** may result in additional fault scenarios, such as causing fires **350**. In embodiments in which one or more of the sensor devices **100** are coupled to the channels **320**, the sensor devices **100** may be rendered inoperable in the third fault scenario **336**. In these and other embodiments, failure of the sensor devices **100** may be detected by a processor and/or server communicatively coupled to the sensor devices **100**. The failure of the sensor device **100** may be treated as sensor data that provides information about the fault scenario.

In some circumstances, damage to the utility infrastructure may include destruction of one or more support **310** structures and/or failure, de-energization, or destruction of one or more channels **320** (e.g., power lines), as depicted in the third fault scenario **336** or the fourth fault cause **338**. In some embodiments, destruction of the support structures **310** and/or failure, de-energization, or destruction of the one or more channels **320** may be detectable by the sensor devices **100**. For example, destruction of the support structures **310** may be detected based on gyroscopic data collected by one or more of the sensor devices **100** coupled to the destroyed support structures **310**. As another example, the orientation of the support structures **310** may typically be fixed or oscillating during normal operation of the utility infrastructure, and a gyroscope included in the sensor devices **100** may detect a change in orientation of the support structures **310** corresponding to destruction of the support structure **310**.

In other embodiments, destruction of one or more support structures **310** (e.g., when one or more of the support structures **310** falls/topples over or collapses) and/or failure, de-energization, or destruction of one or more channels **320** (e.g., power lines) may be detected based on electric-field (E-field) measurements or E-field data collected by the electrometer of a sensor device **100**. For example, the server **240** and/or the analysis device **250** can detect that a support structure **310** has fallen or collapsed based on E-field measurements or E-field data collected by the electrometer of a sensor device **100** coupled to the support structure **310**.

that has fallen over. Also, for example, the server **240** and/or the analysis device **250** can detect that a support structure **310** has fallen or collapsed based on E-field measurements or E-field data collected by the electrometer of a sensor device **100** coupled to a support structure **310** coupled to the fallen/collapsed support structure **310** via channels **220**. As an additional example, the server **240** and/or the analysis device **250** can detect that one or more channels **320** (e.g., power lines) has failed, de-energized, or fallen based on E-field measurements or E-field data collected by the electrometer of a sensor device **100** coupled to the one or more channels **320** or coupled to the support structure **310** supporting or otherwise connected to the one or more channels **320**.

As a more specific example, the server **240** and/or the analysis device **250** can detect that a support structure **310** has fallen or collapsed when a change in the E-field measured by the electrometer of the sensor device **100** exceeds 15% (e.g., when the change in the E-field measured is approximately 25%). As another example, the server **240** and/or the analysis device **250** can detect that the one or more channels **220** have failed, de-energized, or fallen when a change in the E-field measured by the electrometer of the sensor device **100** exceeds 15% (e.g., when the change in the E-field measured is approximately 25%). The change in the E-field can be measured against a baseline value or a previously measured E-field value. The E-field can be measured in volts per meter (V/m).

FIG. 4 is an example system **400** illustrating sensor data collection by the sensor device and analysis of the collected sensor data according to the present disclosure. The system **400** may include a number of sensor devices **100**, an analysis device **250** and/or server **240**, a sensor data storage **430**, a network **230**, and a user dashboard **450**. The sensor devices **100** may collect sensor data **415** and transmit the sensor data **415** to the server **240** and/or the analysis device **250** via the network **230**. The analysis device **250** and/or the server **240** may obtain the sensor data **415** and/or the training sensor data **435** from the sensor data storage **430** (for example, via the network **230**) to identify fault information **425**, which may be sent to the user dashboard **450** for review by a user. The user dashboard **450** may be displayed via a computing device communicatively coupled to the network **230** such that information concerning the utility infrastructure **200** may be transmitted to and/or received through the user dashboard **450**.

The sensor devices **100** may be any of the sensor devices described and shown with respect to FIGS. 1A-1E. The sensor devices **100** may be configured to collect sensor data **415** at set intervals (e.g., once per second, once every ten seconds, once per minute, etc.) and transmit the collected sensor data **415** via the network **230** such that the analysis device **250** and/or the server **240** may obtain the sensor data **415** for monitoring the utility infrastructure and prevent the utility infrastructure from failing. In some embodiments, the sensor data **415** may include structure-orientation data, gyration data, temperature data, humidity data, atmospheric pressure data, precipitation data, wind velocity data, smoke density data, particulate matter data, gas composition data, magnetic field data, electric field data, microwave radiation data, infrared radiation data, ultraviolet radiation data, visible luminosity data, electromagnetic spectroscopy data, mechanical spectroscopy data, audio data, image data, or video data relating to a given utility infrastructure **200**.

In some embodiments, the sensor devices **100** may be configured to obtain automatic firmware updates via the network **230** such as from the server **240** with which the

sensor devices **100** are communicatively coupled. Additionally or alternatively, the sensor devices **100** may include a rollback feature such that the sensor devices **100** are not rendered inoperable due to new firmware updates. In some embodiments, communications between the sensor devices **100** and the server **240** and/or the analysis device **250** via the network **230** may be encrypted to protect against attacks from malicious actors. Packets of information may be hashed prior to transmission and cryptographically signed and verified when received through the network **230**.

The analysis device **250** may store code and routines configured to enable one or more processors to perform one or more operations. Additionally or alternatively, the analysis device **250** may be implemented using hardware including a processor, a microprocessor (e.g., to perform or control performance of one or more operations), a field-programmable gate array (FPGA), or an application-specific integrated circuit (ASIC). In some other instances, the analysis device **250** may be implemented using a combination of hardware and software. In the present disclosure, operations described as being performed by the analysis device **250** may include operations that the analysis device **250** may direct a corresponding system to perform. The analysis device **250** may be configured to perform a series of operations with respect to the sensor data **415** as described in further detail below.

In some embodiments, the analysis device **250** and/or the server **240** may identify and/or predict occurrence of one or more faults in the utility infrastructure based on the sensor data **415**. The analysis device **250** and/or the server **240** may be configured to relate the sensor data **415** to the physical condition of the utility infrastructure based on heuristics, patterns, and/or rules. For example, normal operation of a given utility infrastructure may include vibrations at a given intensity and/or with a given frequency. Responsive to obtaining vibration data from one or more sensor devices **100** at the given intensity and/or with the given frequency, the analysis device **250** and/or the server **240** may determine that the condition of the given utility infrastructure is normal. As an example, in an electrical utility system, current flow through power lines of the electrical utility system may affect vibration of various components included in the electrical utility system.

Additionally or alternatively, the analysis device **250** and/or the server **240** may determine that a fault may have occurred responsive to obtaining vibration data that differs from the vibration sequence associated with normal operation. As another example, destruction of a given support structure may usually correspond to a given vibration sequence and/or change in orientation of one or more sensor devices **100** as detected by a gyroscope. Responsive to obtaining vibration data including intensity and/or frequency corresponding to the given vibration sequence and/or gyroscopic data indicating a change in orientation of the given support structure, the analysis device **250** and/or the server **240** may determine that a fault may have occurred.

In some embodiments, the analysis device **250** and/or the server **240** can determine a normal operating condition for a utility infrastructure **200** (e.g., the first utility infrastructure **200A**) based on comparing the sensor data **415** associated with the utility infrastructure **200** (e.g., the first utility infrastructure **200A**) to the training sensor data **435** associated with the utility infrastructure **200** (e.g., the first utility infrastructure **200A**) from a previous time period and/or training sensor data **435** associated with one or more other utility infrastructures **200** (e.g., the second utility infrastructures **200B**).

In some embodiments, the analysis device **250** and/or the server **240** may identify and/or predict the occurrence of weather phenomena near the utility infrastructure. In these and other embodiments, the weather phenomena may be treated as faults and/or conditions of the utility infrastructure. The sensor data **415** analyzed to identify and/or predict occurrence of weather phenomena may include metrics such as vibration data, temperature, orientation, etc. Additionally or alternatively, the sensor data **415** may include measurements indicative of weather conditions such as atmospheric pressure, humidity, etc.

For example, properties associated with wind affecting a particular utility infrastructure may be measured by the sensor device **100** based on vibration data, movement data, and/or orientation data. The sensor device **100** may be attached to a component of the particular utility infrastructure that moves responsive to being affected by wind movement, such as power lines of electrical infrastructure. Additionally or alternatively, the sensor device **100** may be suspended from a support structure associated with the particular utility infrastructure such that the sensor device **100** may move in response to wind movement. The wind speed near the particular utility infrastructure may be calculated based on vibration data and/or orientation data collected by the sensor device **100** over a given period of time. Additionally or alternatively, the wind direction may be calculated based on the direction in which the sensor device **100** moves during the given period of time. Based on the wind speed and/or the wind direction, the analysis device **250** and/or the server **240** may identify one or more weather phenomena affecting the utility infrastructure in a particular location.

In some embodiments, the analysis device **250** and/or the server **240** may be configured to assess the ambient health of the utility infrastructure. The analysis device **250** and/or the server **240** may obtain the sensor data **415** as inputs for performing calculations representing the condition of the utility infrastructure. For example, the analysis device **250** and/or the server **240** may be configured to calculate whether a given wooden support structure is affected by heart rot based on impulse data and/or vibration data. In this example, the analysis device **250** and/or the server **240** may perform discrete Fourier transforms on the impulse and/or vibration data and plot the transformed data as one or more density spectra representing the given wooden support structure. The analysis device **250** and/or the server **240** may determine whether the given wooden support structure is experiencing heart rot based on the corresponding density spectra (e.g., as determined by a machine learning model trained to recognize heart rot patterns in density spectra).

In some embodiments, identification and/or prediction of the faults of the utility infrastructure may be based on training sensor data **435**. In these and other embodiments, the training sensor data **435** may include historical sensor data associated with the sensor devices **100**, historical sensor data associated with other sensor devices, test-site sensor data, simulated sensor data (e.g., via a computer model), and/or sensor data associated with spatially adjacent sensors. Fault trends and/or patterns in the training sensor data **435** may be determined by a machine learning model, and the determined fault trends and/or patterns may be used to inform fault detection and prediction based on the obtained sensor data **415**. In some embodiments, the machine learning model may include any suitable machine learning model, such as an artificial neural network or a support-vector machine, trained to identify and/or predict faults based on the training sensor data **435**. In some embodiments,

the analysis device **250**, the server **240**, and the sensor data storage **430** may all be communicatively coupled, such as via the network **230**, such that the analysis device **250** and/or the server **240** may obtain training sensor data **435** from the sensor data storage **430**.

The following describes some ways that the system **400** can identify or predict a fault occurrence associated with utility infrastructure **200**. In this embodiment, the system **400** can comprise one or more sensor devices **100** coupled to a first utility infrastructure **200A** (see, for example, FIG. 2). Each of the sensor devices **100** can comprise an enclosure **110** (see, e.g., FIGS. 1A-1C), one or more internal sensors **136** positioned inside the enclosure **110**, one or more external sensors (e.g., the environmental sensors **134**) positioned, at least partly, outside of the enclosure **110**, one or more antennae (e.g., antennae of wireless communication units), and one or more energy-storage features (e.g., the battery **140**). Each of the sensor devices **100** can also comprise an energy-harvesting feature such as the solar cells or solar panel **115**.

One or more processors of the server **240** and/or the analysis device **250** can be programmed to execute instructions stored as part of one or more non-transitory computer-readable storage media of the server **240** or the analysis device **250**, respectively. The one or more processors of the server **240** or analysis device **250** can be programmed to execute instructions to perform operations including obtaining sensor data **415** from the one or more sensor devices **100**. In some embodiments, the sensor data **415** may include at least one of vibration data, impulse data, orientation data, gyration data, temperature data, humidity data, atmospheric pressure data, precipitation data, wind velocity data, smoke density data, particulate matter data, gas composition data, magnetic field data, electric field data, microwave radiation data, infrared radiation data, ultraviolet radiation data, visible luminosity data, electromagnetic spectroscopy data, mechanical spectroscopy data, audio data, image data, and video data. In certain embodiments, the sensor device(s) **100** that collected the sensor data **415** may process the sensor data **415** by identifying whether the sensor data **415** exceeds a given threshold, falls below a given threshold, equals a given value, follows a given trend, displaying a predetermined pattern, etc. to verify occurrence and/or identification of one or more faults. The sensor data **415** may be collected by the sensor device(s) **100** coupled to the first utility infrastructure **200A**.

The server **240** and/or the analysis device **250** can also obtain training sensor data **435** associated with at least one of the first utility infrastructure **200A** from a previous time period (e.g., stored sensor data from the past which can now be used as training sensor data **435**) and at least one second utility infrastructure **200B** (see, for example, FIG. 2). For example, the training sensor data **435** can be obtained from other sensor device(s) **100** coupled to the at least one second utility infrastructure **200B**. Although FIG. 2 shows the second utility infrastructure **200B** as being coupled to the first utility infrastructure **200A**, it is contemplated by this disclosure that the second utility infrastructure **200B** does not need to be coupled to the first utility infrastructure **200A**.

The server **240** and/or the analysis device **250** can then compare the sensor data **415** obtained from the sensor device(s) **100** coupled to the first utility infrastructure **200A** with the training sensor data **435**. Comparison of the obtained sensor data **415** and the training sensor data **435** (e.g., historical sensor data or sensor data obtained from another sensor device **100** coupled to another utility infrastructure **200**) may be performed based on whether the

sensor data **415** exceeds a given threshold, falls below a given threshold, equals a given value, follows a given trend, displaying a predetermined pattern, etc.

The server **240** and/or the analysis device **250** can then identify or predict a utility fault occurrence based on the comparison between the sensor data **415** and the training sensor data **435**. In some embodiments, the utility infrastructure faults or fault occurrences may include utility infrastructure faults that have recently occurred and/or utility infrastructure faults that are likely to occur in the future. For example, the utility infrastructure faults or fault occurrences may include generation of sparks, arcing events, weather-induced (e.g., wind-induced, rain-induced, etc.) vibrations of utility infrastructure components, other nearby weather phenomena, impact shocks from physical contact with the utility infrastructure, environmental damage (e.g., outbreak of fire or fire damage) near the utility infrastructure, etc. Also, for example, utility infrastructure faults that are likely to occur in the future may be identified based on the sensor data **415**, such as transformer and/or capacitor degradation, cross-arm failure and/or fracturing, particulate matter build-up on utility infrastructure components, deterioration of the utility infrastructure due to the presence of rotten or rotting wood, weakening of electrical connections, accumulation of moisture inside transformers, increased leaning of support structures, etc.

The server **240** and/or the analysis device **250** can also transmit an alert message describing or summarizing the utility infrastructure faults or predicted faults. The alert message may be sent to a user monitoring the utility infrastructures **200** via a user dashboard **450**. The user dashboard **450** may be displayed via a supervisory control and data acquisition (SCADA) system, a smartphone application, a desktop computer, a laptop computer, a tablet computer, etc. In some embodiments, the alert message may include a description of the identified and/or predicted utility infrastructure faults, sensor data **415** associated with the utility infrastructure faults, and/or recommendations on courses of action the user may take via control systems for the utility infrastructure **200**.

In certain embodiments, the fault occurrence/infrastructure fault identified or predicted can be a deterioration of the first utility infrastructure **200A**. For example, the deterioration of the first utility infrastructure **200A** can be caused by heart rot, shell rot, and/or animal or insect damage. Also, for example, the deterioration of the first utility infrastructure **200A** can be caused by accidents, natural disasters, or other environmental events.

In these embodiments, the sensor data **415** obtained from the sensor device(s) **100** can comprise vibration data including a present first oscillatory pattern of the first utility infrastructure **200A** due to current flowing through channels **220** (e.g., power lines, electrical lines, etc.) supported or otherwise coupled to the first utility infrastructure **200A**. Moreover, the training sensor data **435** obtained by the server **240** and/or analysis device **250** can include: (i) a previous first oscillatory pattern of the first utility infrastructure **200A** obtained during a previous time period (e.g., from several days ago, several weeks ago, several months ago, and/or several years ago); (ii) a present second oscillatory pattern of a second utility infrastructure **200B** due to current flowing through channels **220** supported or otherwise coupled to the second utility infrastructure **200B**; and/or (iii) a previous second oscillatory pattern of the second utility infrastructure **200B** due to current flowing through channels **220** supported or otherwise coupled to the second utility infrastructure **200B** obtained during a previous time period

(e.g., from several days ago, several weeks ago, several months ago, and/or several years ago). The server **240** and/or the analysis device **250** can identify or predict a fault occurrence associated with the first utility infrastructure **200A** when the present first oscillatory pattern detected by the sensor device(s) **100** coupled to the first utility infrastructure **200A** is attenuated in comparison to at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and/or the previous second oscillatory pattern.

As a more specific example, at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and/or the previous second oscillatory pattern can be an oscillation at a steady frequency of approximately 120 Hz. In this example, the present first oscillatory pattern can be an oscillation at a frequency of below 120 Hz. As a more specific example, the difference between the present first oscillatory pattern and the previous first oscillatory pattern, the present second oscillatory pattern, and/or the previous second oscillatory pattern can exceed a preset threshold.

In these embodiments, the sensor data **415** obtained from the sensor device(s) **100** can comprise vibration data including a present first oscillatory pattern of the first utility infrastructure **200A** in response to a weather-related phenomenon (e.g., wind or rain) affecting the first utility infrastructure **200A** (including channels **220**—power lines, electrical lines, etc.—supported by or coupled to a support structure **210**). Moreover, the training sensor data **435** obtained by the server **240** and/or analysis device **250** can include: (i) a previous first oscillatory pattern of the first utility infrastructure **200A** in response to a weather-related phenomenon (e.g., wind or rain) affecting the first utility infrastructure **200A** (including channels **220**—power lines, electrical lines, etc.—supported by or coupled to a support structure **210**) obtained during a previous time period (e.g., from several days ago, several weeks ago, several months ago, and/or several years ago); (ii) a present second oscillatory pattern of a second utility infrastructure **200B** in response to a weather-related phenomenon (e.g., wind or rain) affecting the second utility infrastructure **200B** (including channels **220**—power lines, electrical lines, etc.—supported by or coupled to a support structure **210**); and/or (iii) a previous second oscillatory pattern of the second utility infrastructure **200B** in response to a weather-related phenomenon (e.g., wind or rain) affecting the second utility infrastructure **200B** (including channels **220**—power lines, electrical lines, etc.—supported by or coupled to a support structure **210**) obtained during a previous time period (e.g., from several days ago, several weeks ago, several months ago, and/or several years ago). The server **240** and/or the analysis device **250** can identify or predict a fault occurrence associated with the first utility infrastructure **200A** when the present first oscillatory pattern detected by the sensor device(s) **100** coupled to the first utility infrastructure **200A** is attenuated in comparison to at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and/or the previous second oscillatory pattern. As a more specific example, the difference between the present first oscillatory pattern and the previous first oscillatory pattern, the present second oscillatory pattern, and/or the previous second oscillatory pattern can exceed a preset threshold.

As a more specific example, at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and/or the previous second oscillatory pattern can be an oscillation at a frequency of between 10 Hz and 50 Hz. In this example, the present first oscillatory pattern can be an oscillation at a frequency of below the previous first oscil-

latory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern.

One technical problem faced by the applicants is how to identify or predict that the utility infrastructure (e.g., the first utility infrastructure **200A**) is in a state of deterioration when the utility infrastructure shows no visible sign of deterioration or damage. One technical solution discovered and developed by the applicants is to compare a present first oscillatory pattern of the first utility infrastructure due to current flowing through channels coupled to the first utility infrastructure with at least one of a previous first oscillatory pattern of the first utility infrastructure due to current flowing through the channels obtained during the previous time period, a present second oscillatory pattern of a second utility infrastructure due to current flowing through channels coupled to the second utility infrastructure, and a previous second oscillatory pattern of the second utility infrastructure due to current flowing through channels coupled to the second utility infrastructure obtained during the previous time period to identify or predict that the utility infrastructure (e.g., the first utility infrastructure **200A**) is in a state of deterioration. For example, at least one of a server and/or an analysis device can identify or predict that the utility infrastructure (e.g., the first utility infrastructure **200A**) is in a state of deterioration when the present first oscillatory pattern is attenuated in comparison to at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern.

Another technical solution discovered and developed by the applicants is to compare a present first oscillatory pattern of the first utility infrastructure in response to a weather-related phenomenon (e.g., wind or rain) affecting the first utility infrastructure **200A** with at least one of a previous first oscillatory pattern of the first utility infrastructure in response to a weather-related phenomenon (e.g., wind or rain) affecting the first utility infrastructure **200A** obtained during the previous time period, a present second oscillatory pattern of a second utility infrastructure in response to a weather-related phenomenon (e.g., wind or rain) affecting the second utility infrastructure **200B**, and a previous second oscillatory pattern of the second utility infrastructure in response to a weather-related phenomenon (e.g., wind or rain) affecting the second utility infrastructure **200B** obtained during the previous time period to identify or predict that the utility infrastructure (e.g., the first utility infrastructure **200A**) is in a state of deterioration. For example, at least one of a server and/or an analysis device can identify or predict that the utility infrastructure (e.g., the first utility infrastructure **200A**) is in a state of deterioration when the present first oscillatory pattern is attenuated in comparison to at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern. The sensor device(s) **100** disclosed herein are especially well-equipped to undertake such measurements given that the sensor device(s) **100** comprise sensors that can measure the various oscillatory patterns and weather-related phenomena.

In some embodiments, one or more fault occurrences may be identified or predicted by at least one of analog signal processing and/or digital signal processing of the sensor data **415** and the training sensor data **435**. The fault occurrences may be identified or predicted by comparing the processed sensor data **415** against the processed training data **435**. In other embodiments, the fault occurrences may be identified or predicted by a machine learning model trained based on the training sensor data associated with the second utility infrastructures.

The training sensor data **435** may include information identifying faults associated with the training sensor data **435** and/or faults that occurred subsequent to collection of the training sensor data **435** such that the analysis device **250** and/or the server **240** may compare the obtained sensor data **415** to the training sensor data **435** to facilitate identification and/or prediction of faults. For example, one or more faults may be induced in a model and/or a simulation of a given utility infrastructure, and sensor data obtained based on the model and/or the simulation may be provided as training data for the machine learning model. As another example, one or more faults associated with sensors spatially adjacent to the sensor devices **100** (e.g., sensors coupled to nearby support structures) may have been previously identified. The sensor data associated with the spatially adjacent sensors may be provided as training data for the machine learning model for comparison with sensor data **415** obtained by the sensor devices **100**. In these and other examples, the spatially adjacent sensor data may be considered a subset of the training sensor data **435**. Additionally or alternatively, the spatially adjacent sensor data may be obtained concurrently with the sensor data **415** associated with the sensor devices **100**.

In certain embodiments, a fault occurrence of the first utility infrastructure can be identified or predicted by feeding sensor data **415** to at least one of a supervised learning model and an unsupervised learning model and obtaining a prediction from at least one of the supervised learning model and the unsupervised learning model concerning the fault occurrence. The supervised learning model and the unsupervised learning model can be trained using the training sensor data **435** obtained from the first utility infrastructure during a previous time period or training sensor data **435** obtained from a second utility infrastructure during a previous time period or a present time period (i.e., in real-time or near-real-time).

In some embodiments, the fault information **425** and/or the sensor data **415** may be stored in the sensor data storage **430**. Additionally or alternatively, the fault information and/or the sensor data may be transmitted to the user dashboard **450** for display and/or storage.

The user dashboard **450** may refer to code and routines configured to enable a computing system to perform one or more operations. Additionally or alternatively, the user dashboard **450** may be displayed on a computing device implemented using hardware including a processor, a microprocessor (e.g., to perform or control performance of one or more operations), a field-programmable gate array (FPGA), or an application-specific integrated circuit (ASIC). In some other instances, the user dashboard **450** may be displayed on a computing device implemented using a combination of hardware and software.

The user dashboard **450** may present an interface with which a supervising user may monitor obtained sensor data, review fault-detection results, and/or interact with the utility infrastructure. In some embodiments, the user dashboard **450** may generate periodic reports summarizing the condition of the utility infrastructure based on the sensor data and fault information provided to the user dashboard **450**. In these and other embodiments, sensor data **415**, training sensor data **435**, and/or fault information **425** displayed via the user dashboard **450** may be downloaded by the user and/or stored in a third-party data storage.

Modifications, additions, or omissions may be made to the system **400** without departing from the scope of the disclosure. For example, the designations of different elements in the manner described is meant to help explain concepts

described herein and is not limiting. For instance, in some embodiments, the sensor devices **100**, the analysis device **250**, the server **240**, and/or the sensor data storage **430**, the network **230**, and the user dashboard **450** are delineated in the specific manner described to help with explaining concepts described herein but such delineation is not meant to be limiting. Further, the system **400** may include any number of other elements or may be implemented within other systems or contexts than those described.

FIG. **5** is a flowchart of an example method **500** of sensor data collection and analysis according to the present disclosure. The method **500** may be performed by any suitable system, apparatus, or device. For example, the analysis device **250** and/or the server **240** may perform one or more of the operations associated with the method **500**. Although illustrated with discrete blocks, the steps and operations associated with one or more of the blocks of the method **500** may be divided into additional blocks, combined into fewer blocks, or eliminated, depending on the particular implementation.

The method **500** may begin at block **510**, where sensor data **415** may be obtained by the server **240** and/or the analysis device **250** from one or more sensor devices **100**. In some embodiments, the sensor data **415** may include at least one of vibration data, impulse data, orientation data, gyration data, temperature data, humidity data, atmospheric pressure data, precipitation data, wind velocity data, smoke density data, particulate matter data, gas composition data, magnetic field data, electric field data, microwave radiation data, infrared radiation data, ultraviolet radiation data, visible luminosity data, electromagnetic spectroscopy data, mechanical spectroscopy data, audio data, image data, and video data. In some embodiments, the sensor device(s) **100** that collected the sensor data **415** may process the sensor data **415** by identifying whether the sensor data **415** exceeds a given threshold, falls below a given threshold, equals a given value, follows a given trend, displaying a predetermined pattern, etc. to verify occurrence and/or identification of one or more faults. The sensor data **415** may be collected by the sensor device(s) **100** coupled to the utility infrastructure **200** as described above in relation to FIGS. **1A**, **1B**, **1C**, **1D**, **1E**, **2**, **3A**, and **3B**.

At block **520**, the obtained sensor data **415** may be compared to training sensor data **435**. In some embodiments, the training sensor data **435** may be obtained from the same sensor device(s) **100** coupled to the utility infrastructure **200** (e.g., the first utility infrastructure **200A**, see FIG. **2**) from a previous time period (e.g., stored sensor data from the past which can now be used as training sensor data **435**). In these and other embodiments, the training sensor data **435** may also be obtained from other sensor device(s) **100** coupled to one or more other utility infrastructures **200** (e.g., the second utility infrastructure **200B**, see FIG. **2**). In certain embodiments, comparison of the obtained sensor data **415** and the training sensor data **435** (e.g., historical sensor data or sensor data obtained from another sensor device **100** coupled to another utility infrastructure **200**) may be performed as described above in relation to FIG. **4**.

At block **530**, one or more utility infrastructure faults or fault occurrences may be identified and/or predicted based on the comparison between the sensor data **415** and the training sensor data **435**. In some embodiments, the utility infrastructure faults or fault occurrences may include utility infrastructure faults that have recently occurred and/or utility infrastructure faults that are likely to occur in the future. For example, the utility infrastructure faults or fault occurrences may include generation of sparks, arcing events,

weather-induced (e.g., wind-induced, rain-induced, etc.) vibrations of utility infrastructure components, other nearby weather conditions, impact shocks from physical contact with the utility infrastructure, environmental damage (e.g., outbreak of fire or fire damage) near the utility infrastructure, etc. Also, for example, utility infrastructure faults that are likely to occur in the future may be identified based on the sensor data **415**, such as transformer and/or capacitor degradation, cross-arm failure and/or fracturing, particulate matter build-up on utility infrastructure components, deterioration of the utility infrastructure due to the presence of rotten or rotting wood, weakening of electrical connections, accumulation of moisture inside transformers, increased leaning of support structures, etc.

At block **540**, an alert message may be generated summarizing the utility infrastructure faults. The alert message may be sent to a user monitoring the utility infrastructure via a user dashboard **450**. The user dashboard **450** may be displayed via a supervisory control and data acquisition (SCADA) system, a smartphone application, a desktop computer, a laptop computer, a tablet computer, etc. In some embodiments, the alert message may include a description of the identified and/or predicted utility infrastructure faults, sensor data **415** associated with the utility infrastructure faults, and/or recommendations on courses of action the user may take via control systems for the utility infrastructure **200**.

Modifications, additions, or omissions may be made to the method **500** without departing from the scope of the disclosure. For example, the designations of different elements in the manner described is meant to help explain concepts described herein and is not limiting. Further, the method **500** may include any number of other elements or may be implemented within other systems or contexts than those described.

FIG. **6** illustrates an example computing system **600**, according to at least one embodiment described in the present disclosure. The computing system **600** may include a processor **610**, a memory **620**, a data storage **630**, and/or a communication unit **640**, which all may be communicatively coupled. Any or all of the devices or servers included as part of the system **400** of FIG. **4** may be implemented as the computing system **600**, including the sensor devices **100**, the analysis device **250**, the server **240**, the sensor data storage **430**, and/or the computing device displaying the user dashboard **450**.

Generally, the processor **610** may include any suitable special-purpose or general-purpose computer, computing entity, or processing device including various computer hardware or software modules and may be configured to execute instructions stored on any applicable computer-readable storage media. For example, the processor **610** may include a microprocessor, a microcontroller, a digital signal processor (DSP), an application-specific integrated circuit (ASIC), a Field-Programmable Gate Array (FPGA), or any other digital or analog circuitry configured to interpret and/or to execute program instructions and/or to process data.

Although illustrated as a single processor in FIG. **6**, it is understood that the processor **610** may include any number of processors distributed across any number of network or physical locations that are configured to perform individually or collectively any number of operations described in the present disclosure. In some embodiments, the processor **610** may interpret and/or execute program instructions and/or process data stored in the memory **620**, the data storage **630**, or the memory **620** and the data storage **630**. In some

embodiments, the processor **610** may fetch program instructions from the data storage **630** and load the program instructions into the memory **620**.

After the program instructions are loaded into the memory **620**, the processor **610** may execute the program instructions, such as instructions to perform the method **500** of FIG. **5**. For example, the processor **610** may obtain instructions regarding obtaining sensor data, comparing sensor data to training sensor data, identifying or predicting utility infrastructure faults, and/or generating alert messages summarizing detected faults.

The memory **620** and the data storage **630** may include computer-readable storage media or one or more computer-readable storage mediums for carrying or having computer-executable instructions or data structures stored thereon. Such computer-readable storage media may be any available media that may be accessed by a general-purpose or special-purpose computer, such as the processor **610**. For example, the memory **620** and/or the data storage **630** may store obtained sensor data (such as the sensor data **415** of FIG. **4**). In some embodiments, the computing system **600** may or may not include either of the memory **620** and the data storage **630**.

By way of example, and not limitation, such computer-readable storage media may include non-transitory computer-readable storage media including Random Access Memory (RAM), Read-Only Memory (ROM), Electrically Erasable Programmable Read-Only Memory (EEPROM), Compact Disc Read-Only Memory (CD-ROM) or other optical disk storage, magnetic disk storage or other magnetic storage devices, flash memory devices (e.g., solid state memory devices), or any other storage medium which may be used to carry or store desired program code in the form of computer-executable instructions or data structures and which may be accessed by a general-purpose or special-purpose computer. Combinations of the above may also be included within the scope of computer-readable storage media. Computer-executable instructions may include, for example, instructions and data configured to cause the processor **610** to perform a certain operation or group of operations.

The communication unit **640** may include any component, device, system, or combination thereof that is configured to transmit or receive information over a network. In some embodiments, the communication unit **640** may communicate with other devices at other locations, the same location, or even other components within the same system. For example, the communication unit **640** may include a modem, a network card (wireless or wired), an optical communication device, an infrared communication device, a wireless communication device (such as an antenna), and/or chipset (such as a Bluetooth device, an 802.6 device (e.g., Metropolitan Area Network (MAN)), a WiFi device, a WiMax device, cellular communication facilities, or others), and/or the like. The communication unit **640** may permit data to be exchanged with a network and/or any other devices or systems described in the present disclosure. For example, the communication unit **640** may allow the system **600** to communicate with other systems, such as computing devices and/or other networks.

A number of embodiments have been described. Nevertheless, it will be understood by one of ordinary skill in the art that various changes and modifications can be made to this disclosure without departing from the spirit and scope of the embodiments. Elements of systems, devices, apparatus, and methods shown with any embodiment are exemplary for the specific embodiment and can be used in combination or

otherwise on other embodiments within this disclosure. For example, the steps of any methods depicted in the figures or described in this disclosure do not require the particular order or sequential order shown or described to achieve the desired results. In addition, other steps operations may be provided, or steps or operations may be eliminated or omitted from the described methods or processes to achieve the desired results. Moreover, any components or parts of any apparatus or systems described in this disclosure or depicted in the figures may be removed, eliminated, or omitted to achieve the desired results. In addition, certain components or parts of the systems, devices, or apparatus shown or described herein have been omitted for the sake of succinctness and clarity.

Accordingly, other embodiments are within the scope of the following claims and the specification and/or drawings may be regarded in an illustrative rather than a restrictive sense.

Each of the individual variations or embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other variations or embodiments. Modifications may be made to adapt a particular situation, material, composition of matter, process, process act(s) or step(s) to the objective(s), spirit, or scope of the present invention.

Methods recited herein may be carried out in any order of the recited events that is logically possible, as well as the recited order of events. Moreover, additional steps or operations may be provided or steps or operations may be eliminated to achieve the desired result.

Furthermore, where a range of values is provided, every intervening value between the upper and lower limit of that range and any other stated or intervening value in that stated range is encompassed within the invention. Also, any optional feature of the inventive variations described may be set forth and claimed independently, or in combination with any one or more of the features described herein. For example, a description of a range from 1 to 5 should be considered to have disclosed subranges such as from 1 to 3, from 1 to 4, from 2 to 4, from 2 to 5, from 3 to 5, etc. as well as individual numbers within that range, for example 1.5, 2.5, etc. and any whole or partial increments therebetween.

All existing subject matter mentioned herein (e.g., publications, patents, patent applications) is incorporated by reference herein in its entirety except insofar as the subject matter may conflict with that of the present invention (in which case what is present herein shall prevail). The referenced items are provided solely for their disclosure prior to the filing date of the present application. Nothing herein is to be construed as an admission that the present invention is not entitled to antedate such material by virtue of prior invention.

Reference to a singular item, includes the possibility that there are plural of the same items present. More specifically, as used herein and in the appended claims, the singular forms "a," "an," "said" and "the" include plural referents unless the context clearly dictates otherwise. It is further noted that the claims may be drafted to exclude any optional element. As such, this statement is intended to serve as antecedent basis for use of such exclusive terminology as "solely," "only" and the like in connection with the recitation of claim elements, or use of a "negative" limitation. Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs.

Reference to the phrase “at least one of”, when such phrase modifies a plurality of items or components (or an enumerated list of items or components) means any combination of one or more of those items or components. For example, the phrase “at least one of A, B, and C” means: (i) A; (ii) B; (iii) C; (iv) A, B, and C; (v) A and B; (vi) B and C; or (vii) A and C.

In understanding the scope of the present disclosure, the term “comprising” and its derivatives, as used herein, are intended to be open-ended terms that specify the presence of the stated features, elements, components, groups, integers, and/or steps, but do not exclude the presence of other unstated features, elements, components, groups, integers and/or steps. The foregoing also applies to words having similar meanings such as the terms, “including”, “having” and their derivatives. Also, the terms “part,” “section,” “portion,” “member” “element,” or “component” when used in the singular can have the dual meaning of a single part or a plurality of parts. As used herein, the following directional terms “forward, rearward, above, downward, vertical, horizontal, below, transverse, laterally, and vertically” as well as any other similar directional terms refer to those positions of a device or piece of equipment or those directions of the device or piece of equipment being translated or moved.

Finally, terms of degree such as “substantially”, “about” and “approximately” as used herein mean the specified value or the specified value and a reasonable amount of deviation from the specified value (e.g., a deviation of up to $\pm 0.1\%$, $\pm 1\%$, $\pm 5\%$, or $\pm 10\%$, as such variations are appropriate) such that the end result is not significantly or materially changed. For example, “about 1.0 cm” can be interpreted to mean “1.0 cm” or between “0.9 cm and 1.1 cm.” When terms of degree such as “about” or “approximately” are used to refer to numbers or values that are part of a range, the term can be used to modify both the minimum and maximum numbers or values.

The term “engine” or “module” as used herein can refer to software, firmware, hardware, or a combination thereof. In the case of a software implementation, for instance, these may represent program code that performs specified tasks when executed on a processor (e.g., CPU, GPU, or processor cores therein). The program code can be stored in one or more computer-readable memory or storage devices. Any references to a function, task, or operation performed by an “engine” or “module” can also refer to one or more processors of a device or server programmed to execute such program code to perform the function, task, or operation.

It will be understood by one of ordinary skill in the art that the various methods disclosed herein may be embodied in a non-transitory readable medium, machine-readable medium, and/or a machine accessible medium comprising instructions compatible, readable, and/or executable by a processor or server processor of a machine, device, or computing device. The structures and modules in the figures may be shown as distinct and communicating with only a few specific structures and not others. The structures may be merged with each other, may perform overlapping functions, and may communicate with other structures not shown to be connected in the figures. Accordingly, the specification and/or drawings may be regarded in an illustrative rather than a restrictive sense.

This disclosure is not intended to be limited to the scope of the particular forms set forth, but is intended to cover alternatives, modifications, and equivalents of the variations or embodiments described herein. Further, the scope of the

disclosure fully encompasses other variations or embodiments that may become obvious to those skilled in the art in view of this disclosure.

What is claimed is:

1. A system comprising:

one or more sensor devices coupled to a first utility infrastructure, the sensor devices comprising:
 an enclosure;
 one or more internal sensors positioned inside of the enclosure, one or more external sensors positioned at least partly outside of the enclosure, or a combination thereof;
 one or more antennae; and
 one or more energy-storage features;
 one or more processors of a server or analysis device; and
 one or more non-transitory computer-readable storage media of the server or analysis device configured to store instructions that, in response to being executed, cause the one or more processors to perform operations, the operations comprising:
 obtaining sensor data comprising vibration data from one or more sensor devices coupled to a first utility infrastructure;
 obtaining training sensor data associated with at least one of the first utility infrastructure from a previous time period and one or more second utility infrastructures;
 comparing the sensor data with the training sensor data associated with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures;
 identifying or predicting a fault occurrence associated with the first utility infrastructure based on the comparing the sensor data associated with the first utility infrastructure to the training sensor data associated with the at least one of the first utility infrastructure from the previous time period and the one or more second utility infrastructures, wherein the fault occurrence comprises a deterioration of the first utility infrastructure, wherein the vibration data obtained from the one or more sensor devices comprises a present first oscillatory pattern of the first utility infrastructure due to current flowing through channels coupled to the first utility infrastructure, wherein the training sensor data comprises at least one of a previous first oscillatory pattern of the first utility infrastructure due to current flowing through the channels obtained during the previous time period, a present second oscillatory pattern of a second utility infrastructure due to current flowing through channels coupled to the second utility infrastructure, and a previous second oscillatory pattern of the second utility infrastructure due to current flowing through channels coupled to the second utility infrastructure and obtained during the previous time period, wherein at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern is an oscillation at a frequency between 10 Hz and 50 Hz, and wherein the fault occurrence is identified or predicted when the present first oscillatory pattern is at a frequency below the at least one of the previous first oscillatory pattern, the present second oscillatory pattern, and the previous second oscillatory pattern, wherein the first utility infrastructure is made in part of wood and wherein the

29

deterioration of the first utility infrastructure is caused by at least one of heart rot, rot caused by an insect or animal, and termite damage of the wood making up at least part of the first utility infrastructure; and

transmitting a message, to a computing device, describing the fault occurrence of the first utility infrastructure or summarizing a condition of the first utility infrastructure.

2. The system of claim 1, wherein the sensor data further comprises at least one of structure-orientation data, gyration data, temperature data, humidity data, atmospheric pressure data, precipitation data, wind velocity data, smoke density data, particulate matter data, gas composition data, magnetic field data, electric field data, microwave radiation data, infrared radiation data, ultraviolet radiation data, visible luminosity data, electromagnetic spectroscopy data, mechanical spectroscopy data, audio data, image data, and video data relating to the utility infrastructure.

3. The system of claim 1, wherein each of the one or more sensor devices comprises at least one of a vibrometer, an accelerometer, a gyroscope, an acoustic microphone, a video camera, an ambient temperature sensor, a barometer, a hygrometer, a magnetometer, a smoke detector, a visible light meter or photometer, an ultraviolet (UV) light detector,

30

an infrared (IR) light detector, an anemometer or wind sensor, a particulate meter or counter, an electrometer, a multi-field electromagnetic field (EMF) meter, a radio frequency (RF) meter, and a spectrometer.

5 4. The system of claim 1, wherein the fault occurrence of the first utility infrastructure is identified or predicted by feeding the sensor data to at least one of a supervised learning model and an unsupervised learning model and obtaining a prediction from the at least one of the supervised
10 learning model and the unsupervised learning model concerning the fault occurrence, and wherein the supervised learning model and the unsupervised learning models are trained using the training sensor data.

15 5. The system of claim 1, wherein each of the one or more sensor devices is coupled to the first utility infrastructure at a position at least 3.0 meters above ground level.

20 6. The system of claim 5, wherein each of the one or more sensor devices is coupled to the first utility infrastructure via a bracket fixedly fastened to an exterior side of the first utility infrastructure, and wherein at least one of a vibration sustained by the first utility infrastructure or a channel coupled to the first utility infrastructure is passed through the first utility infrastructure via the bracket to each of the one or more sensor devices.

* * * * *