



(How *Not* To Do)
Global Optimizations

One-Slide Summary

- A **global optimization** changes an entire method (consisting of **multiple** basic blocks).
- We must be **conservative** and only apply global optimizations when they preserve the original **semantics**.
- We use **global flow analyses** to determine if it is OK to apply an optimization.
- Flow analyses are built out of simple **transfer functions** and can work **forwards** or **backwards**.

Lecture Outline

- Global flow analysis
- Global constant propagation
- Liveness analysis

VOLUME 144
NUMBER 31
50 CENTS
GLOBE WEST
NEWS, 82

The Boston Globe

THURSDAY, NOVEMBER 13, 2004

SKY HIGH
Ticket: Along with Parrot,
Katie to go
TENNIS: Warty among and will
Eight 2004
How tall: 4:10 a.m., 4:47 p.m.
Price: Market: Page 102

INCREDIBLE... NO NEWS

All around the world nothing happened

By Dan Shugrower
PHOTO BY AP/WIDEWORLD

NO
IMAGE



and Amy Swenson celebrating last night at the Athens Sports Depot.

By Michele Kurtz
and Scott R. Grossberger

Today like yesterday

Inside Today

Nothing to tell

By Michael Probyn

NO NEWS

Nothing to nothing

By Anne E. Korndt

NO IMAGE

BETTER TOMORROW

Boston.com



06136
0 947725

ENGIN, Page 47

Local Optimization

Recall the simple basic-block optimizations


- Constant propagation
- Dead code elimination

$X := 3$	\longrightarrow	$X := 3$	\longrightarrow	$X := 3$
$Y := Z * W$		$Y := Z * W$		$Y := Z * W$
$Q := X + Y$		$Q := 3 + Y$		$Q := 3 + Y$




Global Optimization

These optimizations can be extended to an entire control-flow graph




Global Optimization

These optimizations can be extended to an entire control-flow graph




Global Optimization

These optimizations can be extended to an entire control-flow graph



Correctness

- How do we know it is OK to globally propagate constants?
- There are situations where it is incorrect:



Correctness (Cont.)

To replace a use of x by a constant k we must know this **correctness condition**:

*On every path to the use of x , the last assignment to x is $x := k$ ***

Test:

1. What important event took place on December 16, 1773?




I do NOT BELIEVE IN LINEAR TIME. THERE IS NO PAST AND FUTURE: ALL IS ONE, AND EXISTENCE IN THE TEMPORAL SENSE IS ILLUSORY. THIS QUESTION, THEREFORE, IS MEANINGLESS AND IMPOSSIBLE TO ANSWER.




WHEN IN DOUBT, DENY ALL TERMS AND DEFINITIONS.



Example 1 Revisited



Example 2 Revisited




Discussion

- The correctness condition is not trivial to check
- “**All paths**” includes paths around loops and through branches of conditionals
- Checking the condition requires **global analysis**
 - Global = an analysis of the entire control-flow graph for *one* method body

Global Analysis

Global optimization tasks share several traits:

- The optimization depends on knowing a property **P** at a particular point in program execution
- Proving **P** at any point requires knowledge of the entire method body
- Property **P** is typically *undecidable!*



Undecidability of Program Properties

- **Rice's Theorem**: Most interesting dynamic properties of a program are undecidable:
 - Does the program halt on all (some) inputs?
 - This is called the **halting problem**
 - Is the result of a function **F** always positive?
 - *Assume* we can answer this question precisely
 - Take function **H** and find out if it halts by testing function $F(x) = \{ H(x); \text{return } 1; \}$ whether it has positive result
 - *Contradiction!*
- Syntactic properties are decidable!
 - e.g., How many occurrences of “**x**” are there?
- Programs without looping are also decidable!


Conservative Program Analyses

- So, we cannot tell for sure that “x” is always 3
 - Then, how can we apply constant propagation?
- It is OK to be **conservative**.



Conservative Program Analyses


- So, we cannot tell for sure that “x” is always 3
 - Then, how can we apply constant propagation?
- It is OK to be **conservative**. If the optimization requires **P** to be true, then want to know either
 - **P** is definitely true
 - Don't know if **P** is true
- Let's call this *truthiness*




Conservative Program Analyses

- So, we cannot tell for sure that “x” is always 3
 - Then, how can we apply constant propagation?
- It is OK to be **conservative**. If the optimization requires **P** to be true, then want to know either
 - **P** is definitely true
 - Don't know if **P** is true
- It is always correct to say “don't know”
 - We try to say don't know as rarely as possible
- All program analyses are conservative


Global Optimization: Review



Global Optimization: Review



Global Optimization: Review




- To replace a use of x by a constant k we must know that:

*On every path to the use of x , the last assignment to x is $x := k$ ***

Review

- The correctness condition is hard to check
- Checking it requires *global* analysis
 - An analysis of the entire control-flow graph for one method body
- We said that was impossible, right?



Global Analysis

- **Global dataflow analysis** is a standard technique for solving problems with these characteristics
- Global constant propagation is one example of an optimization that requires global dataflow analysis

Global Constant Propagation

- Global constant propagation can be performed at any point where ****** holds
- Consider the case of computing ****** for a single variable **X** at all program points
- Valid points cannot hide!
- We will find you!
 - *(sometimes)*



DISGUISE SKILL

Try harder


Global Constant Propagation (Cont.)

- To make the problem precise, we associate one of the following values with X *at every program point*

<i>value</i>	<i>interpretation</i>
#	This statement is not reachable
c	$X = \text{constant } c$
*	Don't know if X is a constant


Example

Get out a piece of paper. Let's fill in these blanks now.



Recall: # = not reachable, c = constant, * = don't know.

Example Answers




Using the Information

- Given global constant information, it is easy to perform the optimization
 - Simply inspect the $x = ?$ associated with a statement using x
 - If x is constant at that point replace that use of x by the constant
- But how do we compute the properties $x = ?$

The Idea

*The analysis of a complicated program can be expressed as a combination of **simple rules** relating the change in information between **adjacent statements***



Explanation

- The idea is to “push” or “transfer” information from one statement to the next
- For each statement s , we compute information about the value of x immediately before and after s


$C_{in}(x,s)$ = value of x before s

$C_{out}(x,s)$ = value of x after s

Transfer Functions

- Define a **transfer function** that transfers information from one statement to another


Rule 1



$$C_{\text{out}}(x, s) = \# \text{ if } C_{\text{in}}(x, s) = \#$$


Recall: # = “unreachable code”

Rule 2



$C_{\text{out}}(X, x := c) = c$ if c is a constant


Rule 3



$$C_{\text{out}}(X, x := f(\dots)) = *$$

This is a conservative approximation! It might be possible to figure out that $f(\dots)$ always returns 5, but we won't even try!

Rule 4




$$C_{\text{out}}(x, y := \dots) = C_{\text{in}}(x, y := \dots) \text{ if } x \neq y$$

The Other Half


- Rules 1-4 relate the *in* of a statement to the *out* of the same statement
 - they propagate information across statements
- Now we need rules relating the *out* of one statement to the *in* of the successor statement
 - to propagate information **forward** across CFG edges
- In the following rules, let statement *s* have immediate predecessor statements p_1, \dots, p_n

Rule 5




if $C_{\text{out}}(x, p_i) = *$ for some i , then $C_{\text{in}}(x, s) = *$

Rule 6




if $C_{\text{out}}(x, p_i) = c$ and $C_{\text{out}}(x, p_j) = d$ and $d \neq c$
then $C_{\text{in}}(x, s) = *$

Rule 7



if $C_{\text{out}}(x, p_i) = c$ or $\#$ for all i ,
then $C_{\text{in}}(x, s) = c$

Rule 8




if $C_{\text{out}}(x, p_i) = \#$ for all i ,
then $C_{\text{in}}(x, s) = \#$

An Algorithm

- For every entry s to the program, set $C_{in}(x, s) = *$
- Set $C_{in}(x, s) = C_{out}(x, s) = \#$ everywhere else
- Repeat until all points satisfy 1-8:
 - Pick s not satisfying 1-8 and update using the appropriate rule


The Value

- To understand why we need #, look at a loop



The Value

- To understand why we need #, look at a loop



The Value # (Cont.)


- Because of cycles, all points must have values at all times during the analysis
- Intuitively, assigning some initial value allows the analysis to break cycles
- The initial value # means “so far as we know, control never reaches this point”



Sometimes
all paths
lead to the
same place.


Thus you
need #.

Example




*We are done
when all rules
are satisfied!*

Another Example



Another Example: Answer




Must continue until all rules are satisfied!

Orderings

- We can simplify the presentation of the analysis by ordering the values

$$\# < c < *$$

Drawing a picture with “lower” values drawn lower, we get



Orderings (Cont.)

- * is the greatest value, # is the least
 - All constants are in between and incomparable
- Let *lub* be the least-upper bound in this ordering
- Rules 5-8 can be written using lub:
$$C_{in}(x, s) = \text{lub} \{ C_{out}(x, p) \mid p \text{ is a predecessor of } s \}$$

Termination

- Simply saying “repeat until nothing changes” doesn’t guarantee that eventually nothing changes
- The use of lub explains why the algorithm **terminates**
 - Values start as $\#$ and only *increase*
 - $\#$ can change to a constant, and a constant to $*$
 - Thus, $C_{-}(x, s)$ can change at most twice


Number Crunching

The algorithm is polynomial in program size:

Number of steps =


Number of C_(...) values changed * 2 =

(Number of program statements)² * 2



Liveness Analysis


Once constants have been globally propagated, we would like to eliminate dead code



After constant propagation, $X := 3$ is dead (assuming this is the entire CFG)

Live and Dead

- The first value of x is **dead** (never used)
- The second value of x is **live** (may be used)
- Liveness is an important concept



Liveness

A variable x is live at statement s if

- There exists a statement s' that uses x
- There is a path from s to s'
- That path has **no intervening assignment** to x

Global Dead Code Elimination

- A statement $x := \dots$ is dead code if x is dead after the assignment
- Dead code can be deleted from the program
- But we need liveness information first . . .




DODGE

Should have put more points in it, eh?

Computing Liveness


- We can express liveness in terms of information transferred between adjacent statements, just as in constant propagation
- Liveness is simpler than constant propagation, since it is a boolean property (true or false)

Liveness Rule 1




$L_{in}(x, s) = true$ if s refers to x on the rhs

Liveness Rule 2




$L_{in}(x, x := e) = false$ if e does not refer to x

Liveness Rule 3



$L_{\text{in}}(x, s) = L_{\text{out}}(x, s)$ if s does not refer to x

Liveness Rule 4




$$L_{\text{out}}(x, p) = \vee \{ L_{\text{in}}(x, s) \mid s \text{ a successor of } p \}$$


Algorithm

- Let all $L_(...)$ = false initially
- Repeat process until all statements s satisfy rules 1-4 :
 - Pick s where one of 1-4 does not hold and update using the appropriate rule


Liveness Example



Liveness Example Answers



Liveness Example Answers



Termination

- A value can change from **false** to **true**, but not the other way around
- Each value can change only once, so termination is guaranteed
- Once the analysis is computed, it is simple to eliminate dead code

Forward vs. Backward Analysis

We've seen two kinds of analysis:

Constant propagation is a **forwards** analysis:
information is pushed from inputs to outputs

Liveness is a **backwards** analysis: information is
pushed from outputs back towards inputs

Analysis Analysis

- There are many other global flow analyses
- Most can be classified as either forward or backward
- Most also follow the methodology of local rules relating information between adjacent program points

Homework

- WA6 Due next
- Read chapter 7.7
 - Optional David Bacon article
- **Midterm 2** - Tue Nov 24